



Specifications:
 Operating Voltage: 50V AC/DC
 Current Rating: 1A AC/DC
 Withstand Voltage: 250V AC/Minute
 Contact Resistance: $\leq 30m\Omega$
 Insulation resistance: $\geq 100m\Omega$
 Operating Temperature: $-25^{\circ}C \sim +85^{\circ}C$
 Applicable Wire Sizes: AWG32# ~ 28#
 Material: Nylon66 UL94V-0

P 数	尺寸 (mm)	
	A	B
02Y	1.0	3.0
03Y	2.0	4.0
04Y	3.0	5.0
05Y	4.0	6.0
06Y	5.0	7.0
07Y	6.0	8.0
08Y	7.0	9.0
09Y	8.0	10.0
10Y	9.0	11.0
11Y	10.0	12.0
12Y	11.0	13.0
13Y	12.0	14.0
...
20Y	19.0	21.0

一般公差 TOLERANCES X .±0.40 .XX ±0.20 .X ±0.30 .XXX ±0.10 ANGLES ±2°			深圳市宏利电子有限公司 Shenzhen Holy Electronic Co.,Ltd		
检验尺寸标示 SYMBOLS \odot \ominus INDICATE CLASSIFICATION DIMENSION \odot MARK IS CRITICAL DIM. \ominus MARK IS MAJOR DIM.	工程 图号 SH10HG-nY	制图 (DR) *10/03/22 审核 (CHKD)			
表面处理 (FINISH)	比例 (SCALE) 1:1	单位 (UNITS) mm	核准 (APPD) Rigo Lu		
修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	签名 SIGNATURE	张数 (SHEET) 1 OF 1	SIZE A4 REV 0

△	-	-	-
修订	修改摘要	日期	签名
REV	REVISION DESCRIPTION	DATE	SIGNATURE