



Specifications:
 Operating Voltage: 125V AC/DC
 Current Rating: 1A AC/DC
 Withstand Voltage: 500V AC/Minute
 Contact Resistance: $\leq 20m\Omega$
 Insulation resistance: $\geq 100m\Omega$
 Operating Temperature: $-25^{\circ}C \sim +85^{\circ}C$

P数	尺寸 (mm)	
	A	B
2	1.25	4.25
3	2.50	5.50
4	3.75	6.75
5	5.00	8.00
6	6.25	9.25
7	7.50	10.50
8	8.75	11.75
9	10.00	13.00
10	11.25	14.25
11	12.50	15.50
12	13.75	16.75
13	15.00	18.00
14	16.25	19.25
15	17.50	20.50
20	23.75	26.75

一般公差 TOLERANCES X. ± 0.40 .XX ± 0.20 .X ± 0.30 .XXX ± 0.10 ANGLES $\pm 2^{\circ}$			深圳市宏利电子有限公司 Shenzhen Holy Electronic Co.,Ltd		
检验尺寸标示 SYMBOLS \odot \ominus INDICATE CLASSIFICATION DIMENSION \odot MARK IS CRITICAL DIM. \ominus MARK IS MAJOR DIM.					
表面处理 (FINISH)			品名 MX1.25-nA 直针	核准 (APPD) Rigo Lu	张数 (SHEET) 1 OF 1
比例 (SCALE) 1:1			单位 (UNITS) mm		SIZE A4
修订 REV			修改摘要 REVISION DESCRIPTION		日期 DATE
签名 SIGNATURE					

△	-	-	-
修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	签名 SIGNATURE