



Specifications:
 Operating Voltage: 125V AC/DC
 Current Rating: 1A AC/DC
 Withstand Voltage: 500V AC/Minute
 Contact Resistance: ≤ 30mΩ
 Insulation resistance: ≥ 500mΩ
 Operating Temperature: -25°C ~ +85°C
 Material: Phosphoric copper Tin-plated
 Applicable Wire Sizes: AWG32# ~ 28#

一般公差 TOLERANCES X. ±0.40 .XX ±0.20 .X ±0.30 .XXX ±0.10 ANGLES ±2°		深圳市宏利电子有限公司 Shenzhen Holy Electronic Co.,Ltd	
检验尺寸标示 SYMBOLS INDICATE CLASSIFICATION DIMENSION MARK IS CRITICAL DIM. MARK IS MAJOR DIM.	工程图号 MX125TE	制图 (DR) *10/03/22 审核 (CHKD)	
表面处理 (FINISH)	比例 (SCALE) 1:1	单位 (UNITS) mm	核准 (APPD) Rigo Lu
修订 REV	修改摘要 REVISION DESCRIPTION	日期 DATE	签名 SIGNATURE
		张数 (SHEET) 1 OF 1	尺寸 (SIZE) A4 版本 (REV) 0
